

Zinc Anode

PRIMARY USE

- Anti-corrosion electroplating for steel plate, wire and pipe
- Anti-corrosion electroplating for construction hardware and consumer electronics
- Anti-corrosion electroplating for auto parts

COMPOSITION

Products name		Special High Grade Zinc Anode (SHG)	MA Anode
Chemical composition (%)	Pb	<0.003	<0.003
	Fe	<0.002	<0.002
	Cd	<0.002	<0.002
	Sn	<0.001	<0.001
	Mg	-	0.08-0.12
	Zn	Rest	Rest
Form		Ball/Plate	Plate

FORM/DIMENSION

Form	Type	Weight (kg)	Dimension	
Ball	Ø 27	0.08	27mm diameter	
		Packaging	• Cardboard (20kg) • Flexible container (500kg) • Paletina (500kg)	
Form/Composition Plate		Type	Weight (kg)	LxWxH (mm)
SHG	MA			
○	-	200A	3.5	200×120×20
○	-	300K	4.4	300×100×20
○	-	350A	5.6	350×110×20
○	-	390T	2.7±0.4	390× 90×12±3
○	-	400C	5.8	400×100×20
○	-	400K	7.3	400×100×25
○	-	500B	7.7	500×110×20
○	○	500K	7.3	500×100×20
○	-	530B	9.1	530×110×20
○	○	600A	10.4	600×120×20
○	-	600B	12.5	600×120×25
○	-	700A	11.7	700×120×20
○	○	700K	10.0	700×100×20
○	-	800A	13.0	800×120×20

Form/Composition Plate		Type	Weight (kg)	LxWxH (mm)
SHG	MA			
-	○	900A	14.5	900×120×20
○	○	900K	12.2	900×100×20
○	○	1000A	16.4	1000×120×20
○	-	1000B	20.9	1000×120×25
○	○	1000K	14.3	1000×100×20
-	○	1100K	14.8	1100×100×20
○	-	1200	23.9	1200×120×25
-	○	1200K	15.6	1200×100×25
○	-	430B	15.0	445×150×35
○	-	720	15.0	720×100×30
Form/Composition Other		Type	Weight (kg)	LxWxH (mm)
SHG	MA			
○	-	EZ-7	7.0	205×135or145×39
○	○	6.5K	6.5	402×103×27
○	○	6.5K(split)	1.3	103 ×82 ×27
			Packaging	• Flexible container (500kg /1t)

PACKING STYLE



Type : 6.5K Ingot and bundle



Form : Plate



<https://dowa-zinc.co.jp/>

Importer : DOWA METALS & MINING (THAILAND) CO., LTD.

7/395 Moo6, Mabyangporn, Pluakdaeng, Rayong 21140 Thailand | TEL : +66-33-010-714 FAX : +66-33-017-648

Exporter: DOWA METALS & MINING CO., LTD.

22F, Akihabara UDX, 4-14-1, Sotokanda, Chiyoda-ku, Tokyo, 101-0021 Japan | TEL : +81-3-6847-1270 FAX : +81-3-6847-1280

Manufacturer: AKITA ZINC SOLUTIONS CO., LTD.

1, Sunada, Iijima, Akita, 011-0911 Japan | TEL : +81-18-845-6069 FAX : +81-18-845-8037